



At Ecosure we are leading the way in environmentally friendly packaging solutions



As India's first and largest manufacturer of pulpmolding machinery, we take pride in our commitment to sustainability and innovation. Our mission is simple yet profound: to offer top-of-the-line products that not only meet but exceed international regulations.

Call /WhatsApp --+91 9643762650

Toll-free - 1800 202 3353

www.ecosurepulpmolding.com

Electronic Packaging

It is designed to safeguard fragile and sensitive electronic items during storage, handling, and shipping.

Density: 250 - 400 kg/m³

Load Capacity: Up to 30 kg (depending on the design and thickness)

Shock Absorption: up to 60% - 80%

Thickness: 1.5 mm - 5.0 mm

Moisture Resistance: Up to 85% relative humidity



Automobile Packaging

Automobile packaging specialized solutions designed to protect automotive components.

Density: 300–450 kg/m³

Load Capacity: Up to 60 kg

Shock Absorption: Up to 75%

Thickness: 5 mm–20 mm

Moisture Resistance: Up to 85% relative humidity



TV Unit Packaging

Provide optimal protection for televisions during transit and handling, safeguarding.

Density: 300–450 kg/m³

Load Capacity: Up to 50 kg

Shock Absorption: up to 60% - 80%

Thickness: 3 mm–10 mm (corrugated box)

Moisture Resistance: Up to 85% relative humidity



Mobile Devices Tray

Used to securely hold and protect mobile phones and their accessories during storage and shipping.

Density: 250–450 kg/m³

Load Capacity: Up to 10 kg (depending on the design and thickness)

Shock Absorption: Absorbs up to 90%

Thickness: 1.5 mm–5 mm for molded pulp

Moisture Resistance: Up to 85% relative humidity



Microwave Packaging

Protective molded packaging for safe transportation, ensuring durability and impact resistance.

Density: 300–450 kg/m³

Load Capacity: Up to 50 kg

Shock Absorption: up to 60% - 80%

Thickness: 3 mm–10 mm (corrugated box)

Moisture Resistance: Up to 85% relative humidity



Single Bottle Pack

Provide optimal protection for televisions during transit and handling, safeguarding.

Density: 300–450 kg/m³ for molded pulp

Load Capacity: Up to 20 kg (depending on the design and thickness)

Shock Absorption: up to 60%

Thickness: 3 mm–9 mm (corrugated box))

Moisture Resistance: Up to 85% relative humidity)



Flex Wrap

It is designed to safeguard fragile and sensitive electronic items during storage, handling, and shipping.

Density: 250 - 400 kg/m³

Load Capacity: Up to 25 kg (depending on the design and thickness)

Shock Absorption: up to 85%

Thickness: 1.5 mm - 5.0 mm

Moisture Resistance: Up to 85% relative humidity



Cup Holder Tray

A sturdy and eco-friendly pulp-molded tray designed to securely hold and transport multiple cups with ease.

Density: 300–450 kg/m³

Load Capacity: Up to 50 kg (depending on the design and thickness)

Shock Absorption: up to 60% - 80%

Thickness: 3 mm–10 mm (corrugated box))

Moisture Resistance: Up to 85% relative humidity



Apple Tray with Lid

A protective and eco-friendly pulp-molded tray designed to hold and transport fruits safely.

Density: 250–450 kg/m³

Load Capacity: Up to 10 kg (depending on the design and thickness)

Shock Absorption: Absorbs up to 90%

Thickness: 1.5 mm–5 mm for molded pulp

Moisture Resistance: Up to 85% relative humidity



Food Tray with Lid

A durable and biodegradable pulp-molded tray with a secure lid, ideal for packaging and transporting food items.

Density: 300–450 kg/m³

Load Capacity: Up to 50 kg (depending on the design and thickness)

Shock Absorption: up to 60% - 80%

Thickness: 3 mm–10 mm (corrugated box)

Moisture Resistance: Up to 85% relative humidity



Medical Packaging

Provide optimal protection for televisions during transit and handling, safeguarding.

Density: 300–450 kg/m³ for molded pulp

Load Capacity: Up to 20 kg (depending on the design and thickness)

Shock Absorption: up to 60%

Thickness: 3mm to 9mm (Corrugated box)

Moisture Resistance: Up to 85% relative humidity)



Syrup Stock Item

Specialized packaging designed for the safe and secure transport of syrup formulations, adhering to pharmaceutical standards

Density: 250 - 400 kg/m³

Load Capacity: Up to 25 kg (depending on the design and thickness)

Shock Absorption: up to 85%

Thickness: 1.5 mm - 5.0 mm

Moisture Resistance: Up to 85% relative humidity



Chemical Tray

A sturdy, secure tray designed to safely store and transport chemical products, providing protection from contamination

Density: 300–450 kg/m³

Load Capacity: Up to 50 kg (depending on the design and thickness)

Shock Absorption: up to 60% - 80%

Thickness: 3 mm–10 mm (corrugated box))

Moisture Resistance: Up to 85% relative humidity



Hazardous Holder Packaging

Designed to securely store and transport hazardous materials while ensuring safety and compliance

Density: 250–450 kg/m³

Load Capacity: Up to 10 kg (depending on the design and thickness)

Shock Absorption: Absorbs up to 90%

Thickness: 1.5 mm–5 mm for molded pulp

Moisture Resistance: Up to 85% relative humidity



Holder Tray

Used for transportation and storage, ensuring that items stay in place and are protected from damage during handling.

Density: 300–450 kg/m³

Load Capacity: Up to 50 kg (depending on the design and thickness)

Shock Absorption: up to 60% - 80%

Thickness: 3 mm–10 mm (corrugated box)

Moisture Resistance: Up to 85% relative humidity



Paint Tin Pack

Designed to securely hold paint tins, preventing spills, dents, or damage during storage and transport.

Density: 300–450 kg/m³ for molded pulp

Load Capacity: Up to 20 kg (depending on the design and thickness)

Shock Absorption: up to 60%

Thickness: 3 mm–9 mm (corrugated box))

Moisture Resistance: Up to 85% relative humidity)



Sided Pulp Corner

Designed to cushion and protect product edges during shipping and handling

Density: 300–450 kg/m³

Load Capacity: Up to 50 kg (depending on the design and thickness)

Shock Absorption: up to 60% - 80%

Thickness: 3 mm–10 mm (corrugated box))

Moisture Resistance: Up to 85% relative humidity



Ribbed Sided Corner

Durable edge protectors with ribbed design for enhanced strength, providing superior cushioning and stability during shipping

Density: 250–450 kg/m³

Load Capacity: Up to 10 kg (depending on the design and thickness)

Shock Absorption: Absorbs up to 90%

Thickness: 1.5 mm–5 mm for molded pulp

Moisture Resistance: Up to 85% relative humidity



Plain Sided Corner

Smooth-edge protector ensuring basic cushioning and protection for product corners during handling and transit.

Density: 300–450 kg/m³

Load Capacity: Up to 50 kg (depending on the design and thickness)

Shock Absorption: up to 60% - 80%

Thickness: 3 mm–10 mm (corrugated box)

Moisture Resistance: Up to 85% relative humidity



Call /WhatsApp -+91 9643762650

Toll-free - 1800 202 3353

www.ecosurepulpmolding.com